



APC Power-Saving Back-UPS ES 8 Outlet 550VA 230V CEE 7/7

BE550G-GR



Description: Battery Backup & Surge Protector for Electronics and Computers

Includes : CD with software , Telephone Cable , User Manual

[Product Overview](#)
[Technical Specifications](#)
[Documentation](#)
[Options](#)

Output

[Print Technical Specification](#)

Output power capacity	330Watts / 550VA
Max Configurable Power (Watts)	330Watts / 550VA
Nominal Output Voltage	230V
Output Frequency (sync to mains)	47 - 63 Hz
Output Frequency (not synced)	50Hz +/- 0.1% for 50Hz nominal
Other Output Voltages	220
Topology	Standby
Waveform type	Stepped approximation to a sinewave
Output Connections	(4) Schuko CEE 7 (Battery Backup) (4) Schuko CEE 7 (selector_surgetitle)
Output Voltage Tolerance	+/- 5% static and 100% load step
Transfer Time	6ms typical : 10ms maximum

Input

Nominal Input Voltage	230V
Input frequency	50/60 Hz
Input Connections	Schuko CEE 7/7P
Cord Length	1.83meters
Input voltage range for main operations	180 - 266V
Maximum Input Current	10.0A

Batteries & Runtime

Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof	
Typical recharge time	16hour(s)	
Replacement Battery	APCRBC110	
Expected Battery Life (years)	3 - 5	
Battery Volt-Amp-Hour Capacity	86	
Runtime	View Runtime Graph	View Runtime Chart
Efficiency	View Efficiency Graph	

Communications & Management



Surge Protection and Filtering

Surge energy rating	310Joules
Data Line Protection	Analog phone line for phone/fax/modem/DSL (RJ-11 connector), Network line - 10/100 Base-T Ethernet (RJ-45 connector)
Filtering	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449

Physical

Maximum Height	89mm , 8.9cm
Maximum Width	224mm , 22.4cm
Maximum Depth	311mm , 31.1cm
Net Weight	6.02kg
Shipping weight	6.93kg
Shipping Height	127mm , 12.7cm
Shipping Width	279mm , 27.9cm
Shipping Depth	400mm , 40.0cm
Color	Black
Master Carton Dimensions (Length x Width x Height)	324mm
Master Carton Units	2.0
Master Carton Weight	14.55
Pallet Dimensions	48inches
# of Layers per Pallet	4.0
# of Units per Layer per Pallet	20.0
Pallet Weight	1230.0lbs.
Units per Pallet	48.0
SCC Codes	1073130427166 3

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-9000meters
Storage Temperature	-15 - 40 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-9000meters
Audible noise at 1 meter from surface of unit	40.0dBA

Conformance

Approvals	CE, ENERGY STAR (EU)
Equipment protection policy	Lifetime : 100000 Euro
Standard warranty	2 years repair or replace, 3 years repair or replace for European Union countries

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs
PEP	Available in Documentation tab
EOLI	Available in Documentation tab



Life Is On Schneider Electric

Email

OK

WHO WE ARE

CONNECT WITH US

FIND A RESELLER

Zip/Postal Code

FIND

CATALOG KEYCODE

Enter Key Code

GO



TERMS & CONDITIONS >

PRIVACY STATEMENT >

© 2016, APC by Schneider Electric