

BL MetaBright™ Back Light

Model:MB-BL10x23



Backlighting is one of the most popular forms of vision inspection illumination, providing maximum contrast between object and scene and producing a high contrast image with consistent edge definition. *Metaphase Backlights* combine the latest high brightness LEDs with exclusive optical lensing to create high intensity and uniform (+/- 5%), shadow-free illumination.

Connectorized and convenient 24VDC power supply features an onboard and integrated driver. Commonly applied to measuring, defect and hole detection, and determining the orientation of parts. *Metaphase* offers variety of backlights to suit the needs of various applications: area, linear, narrow, and our highly compact thin backlights. Backlights can be configured for wavelength and other specifications.

BENEFITS:

- Up to 50 SMD LED's per inch array
- Exclusive optical lens provides high uniformity (+/- 5%), shadow-free backlight illumination
- High Density Precision Chip Technology (HDPCT)
- Patent-pending thermal management design draws heat directly from the die ensuring long life
- Metaphase Technologies has the largest selection of Backlights in the vision industry.
- Backlights with in-line and built-in strobe circuit available
- Backlight shapes/sizes include low profile, narrow and large area backlights
- Options include built-in line remote & potentiometer intensity control

APPLICATIONS:

- Absence/Presence of Objects
- Defect Detection
- Object tracking
- PCB (Printed Circuit Board)
- Web Inspection
- Bottle/Bolt
- Glass Sheet
- Sub-pixel

RATINGS:



DOMINANT WAVELENGTH:

Part #	Color	Power Supply
MB-BL10x23-W-24	White 5500K	
MB-BL10x23-R-24	Red 630nm	
MB-BL10x23-B-24	Blue 470nm (Optional 455nm)	
MB-BL10x23-G-24	Green 530nm	24 volt power supply available upon request.
MB-BL10x23-IRN-24	Infrared 850nm	
MB-BL10x23-IRL-24	Infrared 880nm	
MB-BL10x23-UVL-24	UV 395nm	
MB-BL10x23-UVS-24	UV 365nm	

10 ft. flying leads come standard on all products.
Light features built-in constant current driver.
No expensive controller required.

Vision Light Tech B.V.

Protonenlaan 22, 5405 NE UDEN, P.O. Box 345, 5400 AH UDEN, The Netherlands

Phone: +31 (0)413 26 00 67, Fax +31 (0)413 26 09 38, E-mail: inquiry@vlt.nl, Website: www.vlt.nl

Trade register No. 17150044, VAT No. NL8112.30.946.B01

BL MetaBright™ Back Light

Model:MB-BL10x23



Vision Light Tech
creating optical solutions

ELECTRICAL & CONTROLS:

Current Consumption	0.7A
Light Intensity	+/-5%
Illuminance	37,000 Lux
Operating Temperature	-22°F(-30°C) to 120°F (60°C)
Lifetime Hours	75,000 Hours

HOUSING:

Dimensions	Length: 1.5in/38.1mm Width: .75in/19.1mm Height: 1.25in/31.8mm
Weight	.25lb/ 113.398g
Housing	Aluminum
Finish	Black Anodized

WIRING DIAGRAM:


RED	+24VDC
WHITE	Ground

24 AWG 2 WIRE CABLE X 1

When not using intensity control, connect 0-10V control line to +24 and intensity control ground to ground

WIRING DIAGRAM:

PIN #	Function
1	+24VDC
2	(N/C)
3	Ground
4	(N/C)



ORDERING INFORMATION:

• M B - B L 1 0 x 2 3 - □ - 2 4 - □

W- White 6000k
R- Red 630nm
G- Green 530nm
B- Blue 470 nm
IRN- Infrared 850nm
IRL- Infrared 880nm
UVL- (long) 395nm
UVS- (short) 365nm

***BLANK**- 10 ft. Flying Leads
T- M12 Quick Disconnect
ILD- In Line Dimmer
ILS- In Line Strobe (customer provide trigger info)

Vision Light Tech B.V.

Protonenlaan 22, 5405 NE UDEN, P.O. Box 345, 5400 AH UDEN, The Netherlands

Phone: +31 (0)413 26 00 67, Fax +31 (0)413 26 09 38, E-mail: inquiry@vlt.nl, Website: www.vlt.nl

Trade register No. 17150044, VAT No. NL8112.30.946.B01

BL MetaBright™ Back Light

Model:MB-BL10x23

DRAWING & DETAILS:

