


MetaBright™ Area Backlight

Model#: MB-BL8X32



- Up to 50 SMD LED's per inch array makes our backlights the brightest most stable backlights in the industry
- Exclusive optical lens producing even (+/- 5%), shadow-free illumination
- High Density Precision Chip technology
- Patent-pending thermal management design draws heat directly from the die ensuring long life
- Stable, flicker-free illumination with instant-start operation

Wiring Diagram		M12 Connector		Specifications:	
Flying Leads	Function	PIN #	Function		
RED	+24VDC	1	+24VDC	Current Consumption	4 ~ 6 Amp @ 24Vdc
BLACK	Ground	3	Ground	Housing	Aluminum
WHITE	+24VDC			Finish	Powder Coated Black
GREEN	Ground			Intensity Uniformity	+/-5%
				Operating Temperature	120° F Max
				Illuminance	37,000 Lux
				Compliance	CE/RoHS
				Lifetime Hours	75,000 Hours



Active Area	Dimensions
8in x 32in	13.6 in x 37.48 in x 1 in
203.2mm x 812.8mm	40.64mm x 951.99mm x 25.4mm

ORDERING INFORMATION:

• MB - BL 8 X 3 2	-	<input type="checkbox"/>	- 2 4 -	<input type="checkbox"/>	
		W	White 6000k	*BLANK	10 ft. Flying Leads
		R	Red 630nm	T	M12 Quick Disconnect
		G	Green 530nm	ILD	In Line Dimmer
		B	Blue 455 nm	ILS	In Line Strobe (customer provide trigger info)
		IR	Infrared 880nm		
		UVL	(long) 395nm		
		UVS	(short) 365nm		

