

# MetaBright™ Linear Front Light

Model#: MB-LFL1X6



- Shock and Vibration proof up to 10 G's per MIL-STD-910F the highest industry standards
- Solid one-piece machined aluminum housings and thermal potting
- Performance extends to rugged environments
- Can be configured for wavelength and other specifications
- Equipt with pairing and axial rotation capabilities

Part #	Color	Power Supply	Specifications:	
MB-LFL1X6-W-24	White 5500K	24 volt power supply available upon request.	Current Consumption	.35A
MB-LFL1X6-R-24	Red 630nm		Housing	Aluminum
MB-LFL1X6-B-24	Blue 455nm		Finish	Anodized
MB-LFL1X6-G-24	Green 530nm		Intensity Uniformity	+/-5%
MB-LFL1X6-IRN-24	Infrared 850nm		Operating Temperature	120° F Max
MB-LFL1X6-IRL-24	Infrared 880nm		Illuminance	120,000 Lux
MB-LFL1X6-UVL-24	UV 395nm		Compliance	CE/RoHS
MB-LFL1X6-UVS-24	UV 365nm		Lifetime Hours	75,000 Hours

10 ft. flying leads come standard on all products.  
Light features built-in constant current driver.  
No expensive controller required.

Active Area	Dimensions
.63in x 6.41in 16mm x 162.7mm	6.6in x .86in 168.3mm x 22mm

## ORDERING INFORMATION:

• M B - L F L 1 X 6 -  - 2 4 -

<b>W</b>	White 5500k	<b>*BLANK</b>	10 ft. Flying Leads
<b>R</b>	Red 630nm	<b>T</b>	M12 Quick Disconnect
<b>G</b>	Green 530nm	<b>ILD</b>	In Line Dimmer
<b>B</b>	Blue 455 nm	<b>ILS</b>	In Line Strobe (customer provide trigger info)
<b>IRL</b>	Infrared 880nm		
<b>UVL</b>	(long) 395nm		
<b>UVS</b>	(short) 365nm		

### Vision Light Tech B.V.

Protonenlaan 22, 5405 NE UDEN, P.O. Box 345, 5400 AH UDEN, The Netherlands  
Phone: +31 (0)413 26 00 67, Fax +31 (0)413 26 09 38, E-mail: inquiry@vlt.nl, Website: www.vlt.nl  
Trade register No. 17150044, VAT No. NL8112.30.946.B01




# MetaBright™ Linear Front Light

Model#: MB-LFL1X6

## M12 Connector

PIN #	Function
1	+24VDC
2	0-10VDC Intensity Control
3	Ground
4	Signal Ground



## Wiring Diagram

Flying Leads	Function
RED	+24VDC
BLACK	Ground
WHITE	+24VDC
GREEN	Ground

24 AWG 4 WIRES CABLE X 1  
When not using intensity control, connect 0-10V control line to +24 (Max Intensity Control = 25V) and intensity control ground to ground

## Drawing/Diagram

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	A	REDRAWN IN SOLIDWORKS, KW	3/16/2012	

<p><b>PROPRIETARY AND CONFIDENTIAL</b> THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF VISION LIGHT TECH. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF VISION LIGHT TECH IS PROHIBITED.</p>	<p>UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ±1/64 ANGULAR: MACH 1/2 °MIND ±5° TWO PLACE DECIMAL ±.01 THREE PLACE DECIMAL ±.005</p>	<p>NAME: KW DATE: 3/16/2012</p>	<p><b>METAPHASE TECHNOLOGIES, INC.</b> TITLE: FRONT LIGHT, LINEAR, .5 X 6 INCH</p>	
	<p>INTERPRET GEOMETRIC TOLERANCING PER:</p>	<p>DRAWN: KW CHECKED: ENG APPR: MFG APPR: G.A. COMMENTS:</p>	<p>SIZE: <b>B</b> DWG. NO.: <b>LFL1X6</b> SCALE: NTS WEIGHT:</p>	<p>REV: <b>A</b> SHEET 1 OF 1</p>
	<p>APPLICATION: DO NOT SCALE DRAWING</p>	<p>FINISH:</p>		
	<p>NEXT ASSY:</p>	<p>USED ON:</p>		