



E - Bifurcated Light Guide, Randomized, PVC Monocoil Sheathing, Rated for -40°F to 225°F

| Model | Part # | A | B | C | D | E | F | G | L |
|-------|--------------|-----------------|-----------------|-----------------|---|-----------------|-----------------|----------------|-----------------|
| E624 | 002122006024 | | | | | | | | 24" (609.6 mm) |
| E636 | 002122006036 | | | | | | | | 36" (914.4 mm) |
| E648 | 002122006048 | | | | | | | | 48" (1219.2 mm) |
| E660 | 002122006060 | | | | | | | | 60" (1523 mm) |
| E672 | 002122006072 | | | | | | | | 72" (1828.8 mm) |
| E824 | 002122008024 | | .187" (4.75 mm) | .250" (6.3 mm) | | | | .50" (12.7 mm) | 24" (609.6 mm) |
| E836 | 002122008036 | | .187" (4.75 mm) | .250" (6.3 mm) | | | | .50" (12.7 mm) | 36" (914.4 mm) |
| E848 | 002122008048 | | .187" (4.75 mm) | .250" (6.3 mm) | | | | .50" (12.7 mm) | 48" (1219.2 mm) |
| E848M | 002122530048 | .125" (3.18 mm) | .588" (15 mm) | .615" (15.6 mm) | | .250" (6.3 mm) | .187" (4.75 mm) | .83" (21 mm) | 48" (1219.2 mm) |
| E860 | 002122008060 | | .187" (4.75 mm) | .250" (6.3 mm) | | | | .50" (12.7 mm) | 60" (1523 mm) |
| E872 | 002122008072 | | .187" (4.75 mm) | .250" (6.3 mm) | | | | .50" (12.7 mm) | 72" (1828.8 mm) |
| E896 | 002122008096 | | .187" (4.75 mm) | .250" (6.3 mm) | | | | .50" (12.7 mm) | 96" (2438.4 mm) |
| E524 | SK95900024 | .156" (3.96 mm) | .187" (4.75 mm) | .312" (7.9 mm) | | .312" (7.9 mm) | .187" (4.75 mm) | .50" (12.7 mm) | 24" (609.6 mm) |
| E536 | SK95900036 | | | | | | | | 36" (914.4 mm) |
| E572 | SK95900072 | | | | | | | | 72" (1828.8 mm) |
| E424 | 002122007024 | | .312" (7.9 mm) | .422" (10.7 mm) | | | | .50" (12.7 mm) | 24" (609.6 mm) |
| E436 | 002122007036 | | .312" (7.9 mm) | .422" (10.7 mm) | | | | .50" (12.7 mm) | 36" (914.4 mm) |
| E448 | 002122007048 | | .312" (7.9 mm) | .422" (10.7 mm) | | | | .50" (12.7 mm) | 48" (1219.2 mm) |
| E448M | 002122424048 | .250" (6.3 mm) | .588" (15 mm) | .615" (15.6 mm) | | .422" (10.7 mm) | .312" (7.9 mm) | .83" (21 mm) | 48" (1219.2 mm) |
| E472 | 002122007072 | | .312" (7.9 mm) | .422" (10.7 mm) | | | | .50" (12.7 mm) | 72" (1828.8 mm) |
| E472M | 002122424072 | | .588" (15 mm) | .615" (15.6 mm) | | | | .83" (21 mm) | 72" (1828.8 mm) |



EX - Bifurcated Light Guide, Randomized, Stainless Steel Sheathing, Rated for -40°F to 225°F

| Model | Part # | A | B | C | D | E | F | G | L |
|-------|--------------|-----------------|-----------------|---|------------------|---|-----------------|----------------|-----------------|
| EX624 | 002124006024 | .063" (1.60 mm) | .187" (4.75 mm) | - | Metal Transition | - | .187" (4.75 mm) | .50" (12.7 mm) | 24" (609.6 mm) |
| EX636 | 002124006036 | | | | | | | | 36" (914.4 mm) |
| EX672 | 002124006072 | | | | | | | | 72" (1828.8 mm) |
| EX824 | 002124008024 | | .187" (4.75 mm) | - | Metal Transition | - | .187" (4.75 mm) | .50" (12.7 mm) | 24" (609.6 mm) |
| EX836 | 002124008036 | .125" (3.18 mm) | .187" (4.75 mm) | - | | | | | 36" (914.4 mm) |
| EX848 | 002124008048 | | | | | | | | 48" (1219.2 mm) |
| EX860 | 002124008060 | | | | | | | | 60" (1523 mm) |
| EX872 | 002124008072 | | | | | | | | 72" (1828.8 mm) |
| EX424 | SK78660024 | .250" (6.3 mm) | .312" (7.9 mm) | - | PVC Heat Shrink | - | .312" (7.9 mm) | .50" (12.7 mm) | 24" (609.6 mm) |
| EX448 | SK78660048 | | | | | | | | 48" (1219.2 mm) |
| EX472 | SK78660072 | | | | | | | | 72" (1828.8 mm) |



EE - Bifurcated Light Guide, Non-Randomized, PVC Monocoil Sheathing, Rated for -40°F to 225°F

| Model | Part # | A | B | C | D | E | F | G | L |
|--------|---------------|--------------------|--------------------|-------------------|-----------------|--------------------|--------------------|-------------------|-----------------|
| EE624 | 0021220106024 | | | | | | | | 24" (609.6 mm) |
| EE636 | 0021220106036 | | | | | | | | 36" (914.4 mm) |
| EE660 | 0021220106060 | .063" (1.60 mm) | .187" (4.75 mm) | .205" (5.2 mm) | PVC Heat Shrink | .205" (5.2 mm) | .187" (4.75 mm) | .50" (12.7 mm) | 60" (1523 mm) |
| EE672 | 0021220106072 | | | | | | | | 72" (1828.8 mm) |
| EE696 | 0021220106096 | | | | | | | | 96" (2438.4 mm) |
| EE824 | 002122008024 | | .187" (4.75 mm) | .250" (6.3 mm) | | | | .50" (12.7 mm) | 24" (609.6 mm) |
| EE836 | 002122008036 | | .187" (4.75 mm) | .250" (6.3 mm) | | | | .50" (12.7 mm) | 36" (914.4 mm) |
| EE836M | 002122360036 | | .588" (15 mm) | .615" (15.6 mm) | | | | .83" (21 mm) | 36" (914.4 mm) |
| EE848 | 002122008048 | | .187" (4.75 mm) | .250" (6.3 mm) | | | | .50" (12.7 mm) | 48" (1219.2 mm) |
| EE860 | 002122008060 | .125" (3.18 mm) | .187" (4.75 mm) | .250" (6.3 mm) | PVC Heat Shrink | .250" (6.3 mm) | .187" (4.75 mm) | .50" (12.7 mm) | 60" (1523 mm) |
| EE860M | 002122360060 | | .588" (15 mm) | .615" (15.6 mm) | | | | .83" (21 mm) | 60" (1523 mm) |
| EE872 | 002122008072 | | .187" (4.75 mm) | .250" (6.3 mm) | | | | .50" (12.7 mm) | 72" (1828.8 mm) |
| EE896 | 002122008096 | | .187" (4.75 mm) | .250" (6.3 mm) | | | | .50" (12.7 mm) | 96" (2438.4 mm) |
| EE8144 | 002122008144 | | .187" (4.75 mm) | .250" (6.3 mm) | | | | .50" (12.7 mm) | 144" (3655 mm) |
| EE8240 | 002122008240 | | .187" (4.75 mm) | .250" (6.3 mm) | | | | .50" (12.7 mm) | 240" (6096 mm) |
| EE412 | 002122014012 | | .312" (7.9 mm) | .422" (10.7 mm) | | | | .50" (12.7 mm) | 12" (305 mm) |
| EE424 | 002122014024 | | .312" (7.9 mm) | .422" (10.7 mm) | | | | .50" (12.7 mm) | 24" (609.6 mm) |
| EE424M | 002122340024 | | .588" (15 mm) | .615" (15.6 mm) | | | | .83" (21 mm) | 24" (609.6 mm) |
| EE436 | 002122014036 | | .312" (7.9 mm) | .422" (10.7 mm) | | | | .50" (12.7 mm) | 36" (914.4 mm) |
| EE436M | 002122340036 | | .588" (15 mm) | .615" (15.6 mm) | | | | .83" (21 mm) | 36" (914.4 mm) |
| EE448 | 002122014048 | .250" (6.3 mm) | .312" (7.9 mm) | .422" (10.7 mm) | PVC Heat Shrink | .422" (10.7 mm) | .312" (7.9 mm) | .50" (12.7 mm) | 48" (1219.2 mm) |
| EE448M | 002122340048 | | .588" (15 mm) | .615" (15.6 mm) | | | | .83" (21 mm) | 48" (1219.2 mm) |
| EE460 | 002122014060 | | .312" (7.9 mm) | .422" (10.7 mm) | | | | .50" (12.7 mm) | 60" (1523 mm) |
| EE460M | 002122340060 | | .588" (15 mm) | .615" (15.6 mm) | | | | .83" (21 mm) | 60" (1523 mm) |
| EE472 | 002122014072 | | .312" (7.9 mm) | .422" (10.7 mm) | | | | .50" (12.7 mm) | 72" (1828.8 mm) |
| EE472M | 002122340072 | | .588" (15 mm) | .615" (15.6 mm) | | | | .83" (21 mm) | 72" (1828.8 mm) |
| EE496 | 002122014096 | | .312" (7.9 mm) | .422" (10.7 mm) | | | | .50" (12.7 mm) | 96" (2438.4 mm) |
| EE4120 | 002122014120 | | .312" (7.9 mm) | .422" (10.7 mm) | | | | .50" (12.7 mm) | 120" (3048 mm) |



EEX - Bifurcated Light Guide, Non-Randomized, Stainless Steel Sheathing, Rated for -40°F to 225°F

| Model | Part # | A | B | C | D | E | F | G | L |
|--------|--------------|--------------------|-----------------|---|------------------|---|--------------------|----------------|-----------------|
| EEX836 | SK78130036 | .125" (3.18 mm) | .187" (4.75 mm) | - | Metal Transition | - | .187" (4.75 mm) | .50" (12.7 mm) | 36" (914.4 mm) |
| EEX524 | 002124075024 | .156" (3.96 mm) | .187" (4.75 mm) | - | Metal Transition | - | .187" (4.75 mm) | .50" (12.7 mm) | 24" (609.6 mm) |
| EEX448 | SK80080048 | | .312" (7.9 mm) | - | PVC Heat Shrink | - | .312" (7.9 mm) | .50" (12.7 mm) | 48" (1219.2 mm) |
| EEX460 | SK80080060 | .250" (6.3 mm) | .312" (7.9 mm) | - | PVC Heat Shrink | - | .312" (7.9 mm) | .50" (12.7 mm) | 60" (1523 mm) |
| EEX472 | SK80080072 | | .312" (7.9 mm) | - | PVC Heat Shrink | - | .312" (7.9 mm) | .50" (12.7 mm) | 72" (1828.8 mm) |
| EEX496 | SK80080096 | | .312" (7.9 mm) | - | PVC Heat Shrink | - | .312" (7.9 mm) | .50" (12.7 mm) | 96" (2438.4 mm) |

Vision Light Tech B.V.

Protonenlaan 22, 5405 NE UDEN, P.O. Box 345, 5400 AH UDEN, The Netherlands

Phone: +31 (0)413 26 00 67, Fax +31 (0)413 26 09 38, E-mail: inquiry@vlt.nl, Website: www.vlt.nl

Trade register No. 17150044, VAT No. NL8112.30.946.B01