


## BT - Threaded End Ferrule, PVC Monocoil Sheathing, Rated for -40°F to 225°F

| Model  | Part #       | A         | B         | C         | L                 | Thread      |
|--------|--------------|-----------|-----------|-----------|-------------------|-------------|
| BT636  | 002112106036 | .063"     | .187"     | .190"     | 36" (914.40 mm)   | 5/16-24 UNF |
| BT672  | 002112106072 | (1.60 mm) | (4.75 mm) | (4.83 mm) | 72" (1828.80 mm)  |             |
| BT824  | 002112108024 |           |           |           | 24" (609.60 mm)   | 5/16-24 UNF |
| BT836  | 002112108036 |           |           |           | 36" (914.40 mm)   |             |
| BT848  | 002112108048 | .125"     | .187"     | .230"     | 48" (1219.20 mm)  |             |
| BT872  | 002112108072 | (3.18 mm) | (4.75 mm) | (5.84 mm) | 72" (1828.80 mm)  |             |
| BT896  | 002112108096 |           |           |           | 96" (2438.40mm)   |             |
| BT8120 | 002112108120 |           |           |           | 120" (3048.01 mm) |             |
| BT536  | SK96830036   | .156"     | .187"     | .268"     | 36" (914.40 mm)   | 5/16-24 UNF |
| BT548  | SK96830048   | (3.96 mm) | (4.75 mm) | (6.81 mm) | 48" (1219.20 mm)  |             |
| BT572  | SK96830072   |           |           |           | 72" (1828.80 mm)  |             |
| BT436  | 700002434036 | .250"     | .312"     | .400"     | 36" (914.40 mm)   | 1/2-20 UNF  |
| BT448  | 700002434048 | (6.35mm)  | (7.92 mm) | (10.15mm) | 48" (1219.20 mm)  |             |
| BT472  | 700002434072 |           |           |           | 72" (1828.80 mm)  |             |



## BXT - Threaded End Ferrule, Stainless Steel Sheathing, Rated for -40°F to 500°F

| Model   | Part #       | A         | B         | C         | L                 | Thread      |
|---------|--------------|-----------|-----------|-----------|-------------------|-------------|
| BXT618  | 002114106018 |           |           |           | 18" (457.20 mm)   | 5/16-24 UNF |
| BXT624  | 002114106024 |           |           |           | 24" (609.60 mm)   |             |
| BXT636  | 002114106036 | .063"     | .187"     | .203"     | 36" (914.40 mm)   |             |
| BXT648  | 002114106048 | (1.60 mm) | (4.75 mm) | (5.16 mm) | 48" (1219.20 mm)  |             |
| BXT672  | 002114106072 |           |           |           | 72" (1828.80 mm)  |             |
| BXT812  | 002114108012 |           |           |           | 12" (304.80 mm)   | 5/16-24 UNF |
| BXT824  | 002114108024 |           |           |           | 24" (609.60 mm)   |             |
| BXT836  | 002114108036 |           |           |           | 36" (914.40 mm)   |             |
| BXT848  | 002114108048 | .125"     | .187"     | .244"     | 48" (1219.20 mm)  |             |
| BXT860  | 002114108060 | (3.18 mm) | (4.75 mm) | (6.20 mm) | 60" (1524.00 mm)  |             |
| BXT872  | 002114108072 |           |           |           | 72" (1828.80 mm)  |             |
| BXT896  | 002114108096 |           |           |           | 96" (2438.40mm)   |             |
| BXT8120 | 002114108120 |           |           |           | 120" (3048.01 mm) |             |
| BXT536  | 002114105036 | .156"     | .187"     | .306"     | 36" (914.40 mm)   | 5/16-24 UNF |
|         |              | (3.96 mm) | (4.75 mm) | (7.77 mm) |                   |             |
| BXT436  | SK83490036   | .250"     | .312"     | .422"     | 36" (914.40 mm)   | 1/2-20 UNF  |
| BXT448  | SK83490048   | (6.35mm)  | (7.92 mm) | (10.7mm)  | 48" (1219.20 mm)  |             |
| BXT460  | SK83490060   |           |           |           | 60" (1524.00 mm)  |             |




### ET - Bifurcated Light Guide, Randomized, PVC Monocoil Sheathing, Threaded End, Rated for -40°F to 225°F

| Model | Part #       | A                  | B           | C                 | D               | E                 | F                  | G                | L                                                                      |
|-------|--------------|--------------------|-------------|-------------------|-----------------|-------------------|--------------------|------------------|------------------------------------------------------------------------|
| ET624 | 002122106024 | .063"<br>(1.60 mm) | 5/16-24 UNF | .312"<br>(7.9 mm) | PVC Heat Shrink | .205"<br>(5.2 mm) | .187"<br>(4.75 mm) | 1.50"<br>(38 mm) | 24" (609.6 mm)<br>36" (914.4 mm)<br>72" (1828.8 mm)                    |
| ET824 | 002122108024 | .125"<br>(3.18 mm) | 5/16-24 UNF | .312"<br>(7.9 mm) | PVC Heat Shrink | .250"<br>(6.3 mm) | .187"<br>(4.75 mm) | 1.50"<br>(38 mm) | 24" (609.6 mm)<br>36" (914.4 mm)<br>48" (1219.2 mm)<br>72" (1828.8 mm) |
| ET536 | 002122105036 | .156"<br>(3.96 mm) | 5/16-24 UNF | .312"<br>(7.9 mm) | PVC Heat Shrink | .250"<br>(6.3 mm) | .187"<br>(4.75 mm) | 1.50"<br>(38 mm) | 36" (914.4 mm)<br>72" (1828.8 mm)                                      |

### EXT, EPXT - Bifurcated Light Guide, Randomized, Stainless Steel Sheathing, Threaded End

| Model   | Part #       | A                  | B           | C                 | D                | E | F                  | G                | L                                                                      |
|---------|--------------|--------------------|-------------|-------------------|------------------|---|--------------------|------------------|------------------------------------------------------------------------|
| EXT624  | 002124106024 | .063"<br>(1.60 mm) | 5/16-24 UNF | .312"<br>(7.9 mm) | Metal Transition | - | .187"<br>(4.75 mm) | 1.50"<br>(38 mm) | 24" (609.6 mm)<br>36" (914.4 mm)<br>72" (1828.8 mm)                    |
| EXT824  | 002124108024 | .125"<br>(3.18 mm) | 5/16-24 UNF | .312"<br>(7.9 mm) | Metal Transition | - | .187"<br>(4.75 mm) | 1.50"<br>(38 mm) | 24" (609.6 mm)<br>36" (914.4 mm)<br>48" (1219.2 mm)<br>72" (1828.8 mm) |
| EPXT624 | 002124316024 | .063"<br>(1.60 mm) | 5/16-24 UNF | .312"<br>(7.9 mm) | PVC Heat Shrink  | - | .187"<br>(4.75 mm) | 1.50"<br>(38 mm) | 24" (609.6 mm)<br>36" (914.4 mm)                                       |
| EPXT824 | 002124318024 | .125"<br>(3.18 mm) | 5/16-24 UNF | .312"<br>(7.9 mm) | PVC Heat Shrink  | - | .187"<br>(4.75 mm) | 1.50"<br>(38 mm) | 24" (609.6 mm)<br>36" (914.4 mm)                                       |



### EET - Bifurcated Light Guide, Randomized, PVC Monocoil Sheathing, Threaded End, Rated for -40°F to 225°F

| Model  | Part #       | A                  | B           | C                 | D               | E                 | F                  | G                | L               |
|--------|--------------|--------------------|-------------|-------------------|-----------------|-------------------|--------------------|------------------|-----------------|
| EET648 | 002122386048 | .063"<br>(1.60 mm) | 5/16-24 UNF | .312"<br>(7.9 mm) | PVC Heat Shrink | .205"<br>(5.2 mm) | .187"<br>(4.75 mm) | 1.50"<br>(38 mm) | 48" (1219.2 mm) |
| EET848 | 002122390048 | .125"<br>(3.18 mm) | 5/16-24 UNF | .312"<br>(7.9 mm) | PVC Heat Shrink | .250"<br>(6.3 mm) | .187"<br>(4.75 mm) | 1.50"<br>(38 mm) | 48" (1219.2 mm) |
| EET548 | 002122370048 | .156"<br>(3.96 mm) | 5/16-24 UNF | .312"<br>(7.9 mm) | PVC Heat Shrink | .250"<br>(6.3 mm) | .187"<br>(4.75 mm) | 1.50"<br>(38 mm) | 48" (1219.2 mm) |

#### Vision Light Tech B.V.

Protonenlaan 22, 5405 NE UDEN, P.O. Box 345, 5400 AH UDEN, The Netherlands

Phone: +31 (0)413 26 00 67, Fax +31 (0)413 26 09 38, E-mail: inquiry@vlt.nl, Website: www.vlt.nl

Trade register No. 17150044, VAT No. NL8112.30.946.B01