



Rev. 5/16

DATA POINTS (TYPICAL)

Wavelength (nm)	Transmission (%)						
1100	0.24	910	0.34	720	0.04	530	0.10
1090	0.36	900	0.54	710	0.05	520	0.10
1080	0.26	890	0.38	700	0.12	510	0.07
1070	0.17	880	0.93	690	0.15	500	0.04
1060	0.14	870	0.57	680	0.11	490	0.05
1050	0.13	860	0.10	670	0.05	480	0.07
1040	0.21	850	0.02	660	0.06	470	0.06
1030	0.37	840	0.02	650	0.04	460	0.05
1020	0.16	830	0.02	640	0.03	450	0.12
1010	0.13	820	0.05	630	0.06	440	0.05
1000	0.19	810	0.11	620	0.06	430	0.20
990	0.22	800	0.08	610	0.03	420	44.67
980	0.23	790	0.04	600	0.07	410	89.84
970	0.20	780	0.03	590	0.04	400	77.67
960	0.28	770	0.06	580	0.14	390	4.75
950	0.31	760	0.06	570	0.07	380	0.04
940	0.20	750	0.04	560	0.06	370	0.02
930	0.39	740	0.20	550	0.09	360	0.03
920	0.26	730	0.10	540	0.14	350	0.09



Vision Light Tech
creating optical solutions